

## Digital Video/Audio D1 Real-Time Recorder

**Model: IDVR-3016**



*\* Optional: DVDRW*

### Features

- 16-CH Analog, D1 Real-time H.264 DVR with Hexaplex operation – record, live, playback, backup, control, & remote access
- H.264 High Profile video compression/decompression with configurable quality
- Max record capabilities – Full-D1: 480/400
- Max playback capabilities – Full-D1: 480/400
- Real-time live display for each channel
- Two-way audio capabilities
- Smart search & playback
- Audio in \* 16 / audio out \* 2
- HDMI \* 1, VGA \* 1, Main monitor \* 1, Call monitor \* 1
- Up to 5 SATA HDDs, or 4 SATA HDDs and 1 DVD
- Alarm in \* 16 / alarm out \* 4, alarm set/unset, panic
- Ethernet and USB 3G dongle support for remote access through I.E. or proprietary remote software, e-mail alarm notification, FTP file storage, remote setup and software upgrade
- Free DDNS server
- Support remote PC with Windows 8/7, Vista, XP, and 2003
- 1 I.E./Firefox software for multiple DVRs
- Remote access through mobile phone/PDA/Tablet PC with free iPhone/iPad/Android software app.
- RS-232 and RS-485 for PTZ, keyboard control, POS, and GPS support
- USB 2.0 for video/audio backup to versatile storage devices
- Internal DVD Models: Video/audio backup to internal DVD, including DVD+RW, DVD+R, and DVD-R
- eSATA connector for HDD extension
- Keypad, remote control, & mouse operation
- Digital watermark
- Multi-lingual support for setup and display
- OCX SDK available for the integration with different applications

## Real-Time recorder

### Specifications

System	O.S.	Embedded Linux 3.0
	Multiplex	Hexaplex operation - simultaneous record, live, playback, backup, control, & remote access
	Certification	FCC, CE, etc.
Video	Format	Analog: NTSC/EIA or PAL/CCIR
	Input	Analog: 16-CH, BNC, 1Vp-p/75ohm
	Main monitor	HDMI x 1, with resolution up to 1920x1080, VGA x 1, with resolution up to 1920x1080, BNC x 1, 1Vp-p/75ohm
	Call monitor	BNC x 1, 1Vp-p/75ohm
	Loss detection	Yes
	Motion detection	Yes, with configurable detection area & sensitivity
	<b>Privacy mask</b>	<b>Yes</b>
Audio	Input	Analog: 16 RCA-jack connectors, line-in level (100mV-2Vrms)
	Output	HDMI, 2 RCA-jack connectors, line-out level (up to 2Vrms)
Record	Compression	<b>Video: H.264 High Profile</b> <b>Audio: ADPCM</b>
	Max frame rate & resolution	Full-D1/Half-D1/CIF: 480/400
	Watermark	Yes
	Mode	Manual/Schedule/Alarm/Motion
	Pre-record time	0 - 10 seconds
	Post-record time	0 - 60 minutes
Display	Resolution	HDMI/VGA – up to 1920x1080 NTSC – 720*480, PAL – 720*576
	Split windows	1/4/7/9/10/13/16
	Frame rate	Up to 30/25 IPS per display window
	Digital Zoom	X2, X4
	Sequential switch	User adjustable
Playback	Max frame rate & resolution	Full-D1/Half-D1/CIF: 480/400
	Search	<b>Smart search</b> , Date/time, Camera, Alarm, & Motion
	Operation	Play, Fast Forward, Backward, Pause, Stop, etc.
Storage	HDD	Up to 5 sets of SATA HDDs with storage > 2TB/HDD Failure detection & privacy law supported
	HDD Extension	1 eSATA connector
	Backup	2 USB 2.0 port <b>Internal DVD models: DVD+RW, DVD+R, DVD-R</b> Self playback for backup files
Alarm	Set/unset	1 contact or TTL/CMOS signal, polarity selectable
	Panic	1 contact or TTL/CMOS signal, polarity selectable

## Real-Time recorder

	Input	16 contact or TTL/CMOS signal, polarity selectable
	Output	2 Normally Open, 2 Normally Closed relay output
	Buzzer	Yes
	Triggered by	Sensor input, Video loss, & Motion
	Event log	Yes
Network	Ethernet	1 RJ-45 10M/100M/1G bps Ethernet connector
	USB 3G dongle	Yes
	Web	Remote setup, monitoring, backup, alarm notification, & remote software upgrade Support Windows 8/7, Vista, XP, and 2003 1 I.E./Firefox for multiple DVRs Configurable HTTP/SMTP/FTP/Control/Data port
	DDNS	<b>Free DDNS server</b>
	E-mail	Alarm notification to stationary or mobile devices
	FTP	Alarm video/audio file storage
	Video	1/4/9/16/25/36/49/64 split-window & SEQ mode for I.E. and HEM Dynamic electronics maps for HEM <b>N-Streaming live view</b>
	Audio	Two-way
	Protocol	TCP/IP, HTTP, PPPoE, DHCP, DDNS, FTP, TSP
	Remote users	Up to 8 users simultaneously
	Bandwidth	TCP/IP type dynamic sliding window control
	Remote stations	<b>PC, mobile phone, PDA, and/or tablet PC With free iPhone/iPad/Android software app.</b>
Control / POS / GPS	Remote Controller	1 remote controller Optional extension cable
	RS-232	1 D-type female connector for PTZ, keyboard, POS, or GPS
	RS-485	2-pin for keyboard/PTZ control
Setup	Local	On screen setup via keypad, remote controller, mouse, and/or RS-485 keyboard
	Remote	Setup & upload via Windows application software
	Multi-lingual	Yes
Reliability	System recovery	Auto power on after power loss recovery
	Watch Dog Timer	Yes
	Timer	Built-in real time clock
	Security	Multi-level password (4 levels, up to 18 accounts)
Weights & Measures	Dimension	430(W) x 350(D) x 66(H)mm
	Weight	4.0 KG (without HDD)
Power	Source	+12VDC
	Consumption	<b>100W Max. (with 5 HDDs)</b>
Operating Temperature		0°C ~ +40°C